

MSQ-A

Primary current:5A-150A
 Secondary current:5A, 1A
 Standard approval:VDE0414,BS7626,IEC185
 Maximum voltage:0.66KV
 Frequency:50-60KV
 Rated load:10VA
 Class:0.5,1.0
 Short-time thermal current:1th=60Ih
 Rated security coefficient:FS5
 Mounting methods:by once-lead or by copper bar

Technical characteristics of current transformers:

WITH BUSBAR



Type	Rated current(A)	Rated power(VA)		Weight(Kg)
		Class:0.5	Class:1	
MSQ-A	30/5	5-10	5-10	0,60
	40/5	5-10	5-10	0,60
	20/5	5-10	5-10	0,60
	60/5	5-10	5-10	0,60
	75/5	5-10	5-10	0,60
	80/5	5-10	5-10	0,60
	100/5	5-10	5-10	0,60
	120/5	5-10	5-10	0,60
	125/5	5-10	5-10	0,60
	200/5	5-10	5-10	0,60
	250/5	5-10	5-10	0,60



WINDOWS TYPE

Bar: 30x10mm conductor: 20mm

Type	Rated current(A)	Rated power(VA)		Weight (Kg)
		Class:0.5	Class:1	
MSQ-30	30/5	-	1	0.4
	40/5	-	1	0.4
	50/5	-	1	0.4
	60/5	-	1	0.4
	75/5	1	1.5	0.4
	80/5	1.5	2.5	0.4
	100/5	2.5	5	0.4
	150/5	5-10	5-10	0.4
	200/5	5-10	5-10	0.4
	250/5	5-10	5-10	0.4
	300/5	5-10	5-10	0.4



WINDOWS TYPE

Bar: 40x10mm conductor: 30mm

Type	Rated current(A)	Rated power(VA)		Weight(Kg)
		Class:0.5	Class:1	
MSQ-40	100/5	2.5	2.5	0.38
	150/5	3	5	0.38
	200/5	5	5-10	0.38
	300/5	5-10	5-10	0.38
	400/5	5-10	5-10	0.38
	500/5	5-10	5-10	0.38

WINDOWS TYPE

Bar: 60x20mm conductor: 40mm



Type	Rated current(A)	Rated power(VA)		Weight (Kg)
		Class:0.5	Class:1	
MSQ-60	250/5	5	5	0.60
	300/5	5	5	0.60
	400/5	5-10	5-10	0.60
	500/5	5-10	5-10	0.60
	600/5	10-15	10-15	0.60
	750/5	10-15	10-15	0.60
	800/5	10-15	10-15	0.60
	1000/5	15	15	0.60

WINDOWS TYPE

Bar: 60x20mm conductor: 80mm



Type	Rated current(A)	Rated power(VA)		Weight (Kg)
		Class:0.5	Class:1	
MSQ-80	750/5	15	15	0.75
	800/5	15	15	0.82
	1000/5	15	15	0.89
	1200/5	15	15	0.99
	1500/5	15	15	1.02

WINDOWS TYPE

Bar: 60x20mm conductor: 80mm



Type	Rated current(A)	Rated power(VA)		Weight (Kg)
		Class:0.5	Class:1	
MSQ-100	1500/5	15	15	0.80
	1600/5	15	15	0.80
	2000/5	15	15	0.94
	2250/5	15	15	0.98
	2500/5	15	15	1.10
	3000/5	15	15	1.16

WINDOWS TYPE

Bar: 60x20mm conductor: 80mm



Type	Rated current(A)	Rated power(VA)		Weight (Kg)
		Class:0.5	Class:1	
MSQ-125	1500/5	15	15	1.0
	2000/5	15	15	1.15
	2500/5	15	15	1.45
	3000/5	15	15	1.60
	4000/5	15	15	1.90
	5000/5	15	15	2.20