

NSQ Series:

Primary current:	30A-3000A
Secondary current:	5A, 1A
Standard approval:	BS7626, IEC44-1
Maximum voltage:	0.66KV
Frequency:	50-60Hz
Rated load:	2.5VA, 15VA
Class:	0.5, 1.0, 3.0
Short-time thermal current:	$I_{th}=60 \times I_h$
Rated security coefficient:	FS<5

Technical data:

Model	Primary/ secondary	Busbar Hole Dimension	Rated Burden (VA)	class	Rated Voltage	Rated Frequency
NSQ-30	30/5A- 300/5A	30×10mm	2.5-5	0.5/1.0	0.72	50/60Hz
NSQ-35	50/5A- 400/5A	35×10mm	5	0.5/1.0	0.72	50/60Hz
NSQ-40	100/5A- 600/5A	40×10mm	10	0.5/1.0	0.72	50/60Hz
NSQ-60	600/5A- 1600/5A	60×10mm	15	0.5/1.0	0.72	50/60Hz
NSQ-100	800/5A- 3000/5A	100×10mm	15	0.5/1.0	0.72	50/60Hz

Dimension of case (mm):

Model	A	B	C	D	E	F
NSQ-30	30	78	46	95	112	70
NSQ-35	40	70	46	84	100	70
NSQ-40	45	80	46	87	104	70
NSQ-60	60	110	53	130	148	80
NSQ-100	100	155	53	174	191	80

Outline Drawing:

