

Pin Shaped Insulated Terminal

1. Specifications

Lead section: 0.5~1.5mm²(22~16) Max current: =19A

ITEM.NO.	FØ (mm)	Dimension (mm)			Color
		L	H	DØ	
PTV1.25-9	1.9	19.0	10.0	4.3	Red
PTV1.25-10	1.9	20.0			
PTV1.25-12	1.9	22.0			
PTV1.25-13	1.9	23.0			

Lead section: 1.5~2.5mm²(16~14) Max current: =27A

ITEM.NO.	FØ (mm)	Dimension (mm)			Color
		L	H	DØ	
PTV2-9	1.9	19.0	10.0	4.9	Blue
PTV2-10	1.9	20.0			
PTV2-12	1.9	22.0			
PTV2-13	1.9	23.0			

Lead section: 4~6mm²(12~10) Max current: =48A

ITEM.NO.	FØ (mm)	Dimension (mm)			Color
		L	H	DØ	
PTV5.5-13	2.8	25.5	12.5	6.7	Yellow

Lead section: 0.5~1.5mm²(22~16) Max current: =19A

ITEM.NO.	Dimension (mm)			C
	W	L	F	
DBV1.25-10	2.3	20.0	10.0	4.3
DBV1.25-11	3.0	21.0	11.0	
DBV1.25-14	3.0	24.0	14.0	
DBV1.25-18	2.3	28.0	18.0	

Lead section: 1.5~2.5mm²(16~14) Max current: =27A

ITEM.NO.	Dimension (mm)			C
	W	L	F	
DBV2-9	2.8	19.0	9.0	4.9
DBV2-18	2.3	28.0	18.0	

Lead section: 4~6mm²(12~10) Max current: =48A

ITEM.NO.	Dimension (mm)			
	W	L	F	C
DBV5.5-10	2.8	22.5	10.0	5.6

