

Ring Shaped Insulated Terminal

1. Specifications

Lead section: 0.5~1.5mm²(22~16) Max current: =9A

ITEM.NO.	Number of ANSI bolt	Diameter of bolt mouth d2	B (mm)	L (mm)	F (mm)	H (mm)	DØ (mm)	Color
RV1.25-3	#4	3.2mm	5.7	17.8	4.95	10.0	4.3	Red
RV1.25-3.5	#6	3.7mm	5.7	17.8	4.95			
RV1.25-3.5	#6	3.7mm	6.6	20.1	6.3			
RV1.25-3.5	#6	3.7mm	8.0	21.5	7.0			
RV1.25-4	#8	4.3mm	6.6	20.1	6.3			
RV1.25-4	#8	4.3mm	8.0	21.5	7.0			
RV1.25-5	#10	5.3mm	8.0	21.5	7.0			
RV1.25-6	1/4	6.5mm	11.6	27.5	11.1			
RV1.25-8	5/16	8.4mm	11.6	27.5	11.1			
RV1.25-10	3/8	10.5mm	13.6	31.6	13.9			

Lead section: 1.5~2.5mm²(16~14) Max current: =27A

ITEM.NO.	Number of ANSI bolt	Diameter of bolt mouth d2	B (mm)	L (mm)	F (mm)	H (mm)	DØ (mm)	Color
RV2-3	#4	3.2mm	6.6	17.8	4.3	10.0	4.9	Blue
RV2-3.5	#6	3.7mm	6.6	17.8	4.3			
RV2-3.5	#6	3.7mm	6.6	21.0	7.0			
RV2-3.5	#6	3.7mm	8.5	22.5	7.75			
RV2-4	#8	4.3mm	6.6	21.0	7.0			
RV2-4	#8	4.3mm	8.5	22.5	7.75			
RV2-5	#10	5.3mm	8.5	22.5	7.75			
RV2-5	#10	5.3mm	9.5	22.5	7.25			
RV2-6	1/4	6.5mm	12.0	27.6	11.0			
RV2-8	5/16	8.4mm	12.0	27.6	11.0			
RV2-10	3/8	10.5mm	13.6	30.2	13.9			

Lead section: 2.5~4mm²(14~12) Max current: =37A

ITEM.NO.	Number of ANSI bolt	Diameter of bolt mouth d2	B (mm)	L (mm)	F (mm)	H (mm)	DØ (mm)	Color
RV3.5-4	#8	4.3mm	8.0	24.5	7.7	12.5	6.2	Black
RVS3.5-5	#10	5.3mm	8.0	24.6	7.7			
RVL3.5-5	#10	5.3mm	12.0	27.9	7.7			
RV3.5-6	1/4	6.5mm	12.0	27.9	7.7			

Lead section: 4~6mm²(12~10) Max current: =48A

ITEM.NO.	Number of ANSI bolt	Diameter of bolt mouth d2	B (mm)	L (mm)	F (mm)	H (mm)	DØ (mm)	Color
RV5.5-3.5	#6	3.7mm	7.2	21.4	5.9	12.5	6.7	Yellow
RV5.5-4	#8	4.3mm	7.2	21.5	5.9			
RV5.5-4	#8	4.3mm	9.5	25.5	8.3			
RV5.5-5	#10	5.3mm	9.5	25.5	8.3			
RV5.5-6	1/4	6.5mm	12.0	31.5	13.0			
RV5.5-8	5/16	8.4mm	15.0	33.7	13.7			
RV5.5-10	3/8	10.5mm	15.0	33.7	13.7			
RV5.5-12	1/2	10.0mm	19.2	30.1	16.0			

