


general terminal

H 2611

wire section (mm²):0.5-4

rated current / voltage : 25A/600V

thick/wide/high : 7/33/41




general terminal

H 2624

wire section (mm²) : 0.5-2.5

rated current / voltage : 25A/600V

thick/wide/high : 7/33/41




general terminal

H 2614

wire section (mm²) : 0.5-2.5

rated current / voltage : 25A/600V

thick/wide/high : 7/33/41




general terminal

H 2600

wire section (mm²):0.5-6

rated current / voltage : 36A/600V

thick/wide/high : 6.5/40/49mm




general terminal

H 2629

wire section (mm²) : 0.5-6

rated current / voltage : 36A/600V

thick/wide/high : 6.5/40/49mm




general terminal

H 2238

wire section (mm²) : 0.5-10

rated current / voltage : 48A/600V

thick/wide/high : 10/40/49mm




general terminal

H 2643

wire section (mm²):0.5-10

rated current / voltage : 48A/600V

thick/wide/high : 10/40/49mm




general terminal

H 2626

wire section (mm²) : 0.5-10

rated current / voltage : 65A/600V

thick/wide/high : 10/52/55mm




general terminal

H 2601

wire section (mm²) : 16-35

rated current / voltage : 115A/600V


thick/wide/high : 18/55/59mm



sign type

H 9006


mm :38x7mm



connecting-ground terminal

H 2603


wire section (mm²) :0.5-6
rated current / voltage : 36A/600V
thick/wide/high :6.5/26/28mm



fuse type

H3852.3853


wire section (mm²) :0.5-10
rated current / voltage :600V
thick/wide/high : 13/54/53mm



test type

H 2608

wire section (mm²):0.5-10
rated current / voltage :25A/600V
thick/wide/high :12/33/41mm



strip terminal

H 3801-6

wire section (mm²) :0.5-6
rated current / voltage : 36A/600V
thick/wide/high :53/21/21mm



strip terminal

H 3801-10

wire section (mm²) :0.5-6
rated current / voltage :36A/600V
thick/wide/high :81/21/21mm



connecting-ground terminal

H 3801-12

wire section (mm²):0.5-6
rated current / voltage :36A/600V
thick/wide/high :92/21/21mm



fuse type

H 2519-2

wire section (mm²) :0.5-6
rated current / voltage : 36A/600V
thick/wide/high :21/21/21mm



test type

H 2519-3

wire section (mm²) :0.5-6
rated current / voltage :36A/600V
thick/wide/high :33/21/21mm



strip terminal

strip terminal

H 2519-5

H 2519-12

wire section (mm²) :0.5-6

wire section (mm²) :0.5-6

rated current / voltage :36A/660V

rated current / voltage :36A/660V

thick/wide/high :50/21/21mm

thick/wide/high: 132/21/21mm