

1.Specification

Material: Nylon 66, 94V-2 certificated by UL. Heat-resisting, erosion control & insulate.

Operating temperature: -40°C to 85°C.

Color: Natural (or white, standard color), UV black and other colors are available as requested.



Item NO.	L(mm)	W(mm)		Bundle diameter (mm)	Min.loop tensile strength	
		Model A25	Model B		LBS	KGS
3 x 60	60	2.5	2	2-11	18	8
3 x 80	80	2.5	2	2-16	18	8
3 x 90	90	2.5	2	2-18	18	8
3 x 100	100	2.5	2.2	2-22	18	8
3 x 120	120	2.5	2.2	2-0	18	8
3 x 140	140	2.5	2.2	2-33	18	8
3 x 150	150	2.5	2.2	2-35	18	8
3 x 160	160	2.5	2.2	2-40	18	8
3 x 200	200	2.5	2.2	3-50	18	8
4 x 140	140	3.5	3.2	3-33	40	18
4 x 150	150	3.5	3.2	3-35	40	18
4 x 180	180	3.5	3.2	3-42	40	18
4 x 200	200	3.5	3.2	3-50	40	18
4 x 250	250	3.5	3.2	3-65	40	18
4 x 280	280	3.5	3.2	3-70	40	18
4 x 300	300	3.5	3.2	3-80	40	18
4 x 370	370	3.5	3.2	3-102	40	18
5 x 120	120	4.8	4.2	3-24	50	22
5 x 180	180	4.8	4.2	3-42	50	22
5 x 190	190	4.8	4.2	3-46	50	22
5 x 200	200	4.8	4.2	3-50	50	22
5 x 250	250	4.8	4.2	3-65	50	22
5 x 280	280	4.8	4.2	3-70	50	22
5 x 300	300	4.8	4.2	3-82	50	22
5 x 350	350	4.8	4.2	3-90	50	22
5 x 380	380	4.8	4.2	3-102	50	22
5 x 400	400	4.8	4.2	3-105	50	22
5 x 430	430	4.8	4.2	3-110	50	22
5 x 450	450	4.8	4.2	3-130	50	22



8 x 150	150	7.0	6.6	3-33	120	55
8 x 180	180	7.0	6.6	3-42	120	55
8 x 200	200	7.0	6.6	3-50	120	55
8 x 250	250	7.0	6.6	4-63	120	55
8 x 300	300	7.0	6.6	4-82	120	55
8 x 350	350	7.9	6.6	4-90	120	55
8 x 400	400	7.9	6.6	4-105	120	55
8 x 450	450	7.9	6.6	4-118	120	55
8 x 500	500	7.9	6.6	4-150	120	55
9 x 550	550	9.0	8.2	8-160	175	80
9 x 650	650	9.0	8.2	8-190	175	80
9 x 760	760	9.0	8.2	10-225	175	80
9 x 920	920	9.0	8.2	10-265	175	80
9 x 1020	1020	9.0	8.2	10-295	175	80
10 x 450	450	10.0	8.2	10-125	200	91
10 x 500	500	10.0	8.2	12-150	200	91
10 x 600	600	10.0	8.2	12-175	200	91
10 x 700	700	10.0	8.2	12-205	200	91
12 x 650	650	12.0	10.5	14-190	250	114
12 x 750	750	12.0	10.5	10-220	250	114