


Application:

It can be used for the insulation resistance tester of the production, inspect units or departments

Features:

- * Resistance range is up to 1000GΩ.
- * Fine temperature stability, can be used in wide range temperature, to ensure accuracy.
- * The Max. input voltage is up to 10kV
- * It has a 0.1F/10kV capacitor and can be used for capacity load test.
- * It has 3 ½ LCD digital voltmeter, input impedance is 10 GΩ, the measuring ranges 19.99kV ; 1999V can be selected



AD 2500

Specifications

Resistor	Resistance Range	10MΩ~ 50MΩ	100MΩ~ 500MΩ	1GΩ~ 100GΩ	200GΩ~ 1000GΩ
	Accuracy	0.2	0.5	1	2
	The Highest Operating Voltage	2500V	5000V	10kV	
Volt meter	Voltage Range	0V ~ 1999V 0V ~ 19.99kV			
	Input Impedance	10GΩ			
	Accuracy	±(0.5 % RDG+1d) ; ±(1 % RDG+1d)			
Operating Temperature & Humidity		23°C±5°C ; < 85 % RH			
Dimensions		595 mm (L) × 305 mm(W) × 160 mm (D)			
Weight		≈ 6.2kg			

Specifications

AD	Material	d(mm)	D (mm)
10	PE	7	10
13	PE	10	13
15.8	PE	13	15.8
18	PE	14	18
21.2	PE	17	21.2
28.5	PE	22.5	28.5
34.5	PE	28.5	34.5
42.5	PE	35	42.5
54.5	PE	43	54.5
10	PA	7	10
13	PA	10	13
15.8	PA	13	15.8
18	PA	14	18
21.2	PA	17	21.2
28.5	PA	22.5	28.5
34.5	PA	28.5	34.5
42.5	PA	35	42.5
54.5	PA	43	54.5



Wave Tube

Drawing

