



CJX5-S-N80



CJX5-S-N50



CJX5-S-N35



CJX5-S-N18

Application

CJX5-S-N series AC contactors are suitable for AC 50Hz, rated voltage up to 660V, mainly used as putting through long distance, breaking circuit and frequently starting control AC motor. It can also be used for counter-connection breaking of squirrel-cage motor in the case of reducing working current.



CJX5-S-N20



CJX5-S-N12



CJX5-S-N25

Specification

Model	Capacity of 3 phase squirrel-cage motor AC-3								Rated heating current 1th(A)
	Rated power (KW)				Rated operating current(A)				
	220-240V	380-440V	550V	660V	220-240V	380-440V	550V	660V	
CJX5-S-N10	2.5	4.0	4.0	4.0	11	9	7	5	20
CJX5-S-N11	3.5	5.5	5.5	5.5	13	12	9	7	20
CJX5-S-N12	3.5	5.5	5.5	5.5	13	12	9	7	20
CJX5-S-N20	5.5	11	11	7.5	22	22	17	9	32
CJX5-S-N21	5.5	11	11	7.5	22	22	17	9	32
CJX5-S-N25	8.5	14	14	14	30	30	12	12	40
CJX5-S-N35	12	20	20	20	40	40	17	17	40