



CJX2-D115NS



CJX2-D205NS

Main datas

Model(CJX2)	Rated insulation voltage	For distribution circuits Rated thermal current	Rated operation current 3p-440V 50/60Hz LL/NL	For distribution circuits Rated operation power for AC3 difference in temperature of load rated motor power					
				200V					
				380V		415/440V			
				Kw	hp	Kw	hp	Kw	hp
D115NS	1000V	200A	NL/LL 115/-	30/-	40/-	55/-	75/-	80/-	80/-
D150NS	1000V	250A	NL/LL 150/-	40/-	55/-	75/-	100/-	80/-	110/-
D170NS	1000V	275A	NL/LL 170/-	45/-	60/-	80/-	110/-	90/-	120/-
D205NS	1000V	275A	NL/LL 205/185	60/55	80/75	100/90	135/125	110/100	150/135
D2054NS	1000V	275A	NL/LL 215/205	65/60	90/80	110/100	150/135	115/110	155/150
D245NS	1000V	315A	NL/LL 245/-	70/-	95/-	120/-	160/-	130/-	175/-
D2454NS	1000V	315A	NL/LL 245/225	70/68	95/90	120/110	160/150	130/120	175/160
D300NS	1000V	400A	NL/LL 300/-	85/-	115/-	150/-	200/-	160/-	215/-
D3004NS	1000V	400A	NL/LL 320/300	90/85	125/115	160/150	215/200	170/160	230/215
D410NS	1000V	500A	NL/LL 410/-	110/-	150/-	210/-	280/-	225/-	305/-
D4104NS	1000V	500A	NL/LL 440/410	120/110	160/150	220/210	300/280	235/225	340/305
D475NS	1000V	700A	NL/LL 475/-	145/-	195/-	250/-	335/-	270/-	360/-
D4754NS	1000V	700A	NL/LL 500/475	150/145	200/195	260/250	350/335	285/270	385/360
D620NS	1000V	1000A	NL/LL 620/-	180/-	240/-	330/-	440/-	400/-	530/-
D6204NS	1000V	1000A	NL/LL 700/620	210/180	280/240	370/330	495/440	425/400	570/530