

1. Features

- Low VA coil for cooler operation and increased life.
- Quiet operation
- Universal style mounting bracket fits existing mounting holes.
- Double break contacts ensure positive make and break.
- Screw terminals or pressure connectors and double 1/4 quick connects provided on all models for easy installation

2. Specifications

Insulating material	Contact block and carrier are high quality electrical-grade thermosetting resin
Temperature range	-40°F to 150°F
Mechanical life (no load)	Conforms to UL and ARI specifications
Electrical life	Conforms to UL and ARI specifications
Weight (approximate)	9.25 oz
Coils Frequency	50/60Hz
Coil insulation	Class B(130°C)
Termination	Pressure connector and double 1/4 Q.C
Operate	85%of nominal coil voltage; 110% maximum safe operate
Duty cycle	Continuous

3. Coil data

Steveco Number 30 Amp 40Amp	Voltage AC	Res DC OHMS	Current MA	Nominal VA	Max. inrush
AMC2-244 AMC2-247	24	11	250	6	32
AMC2-245 AMC2-248	120	224	50	6	32
AMC2-246 AMC2-249	208/240	997	25	6	32

4. Contact ratings

Type	Voltage	FLA	LRA	RES
AMC2-244 thru AMC2-246	277	30	150	40
	480	30	75	40
	600	30	50	40
AMC2-247 thru AMC2-252	277	40	200	50
	480	40	100	50
	600	40	80	50

